



WOODGUARD PROFESSIONNAL - 5201

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : WOODGUARD PROFESSIONNAL
Product code : 5201.
UFI : SHDF-20T0-Q00D-KR5R

1.2. Relevant identified uses of the substance or mixture and uses advised against

Protection product Wood

1.3. Details of the supplier of the safety data sheet

Registered company name : GUARD INDUSTRIE S.A.S..
Address : 7 Rue Gutenberg.93100.Montreuil.France.
Telephone : 0155861760. Fax : 0148581689.
info@guardindustrie.com
www.guardindustrie.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contains substances \geq 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

WOODGUARD PROFESSIONNAL - 5201

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
EC: 406-750-9 A MIXTURE OF: BIS(2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-1,10-DECANEDIOATE;1,8-BIS[(2,2,6,6-TETRAMETHYL-4-((2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-DECAN-1,10-DIOYL)PIPERIDIN-1-YL)OXY]OCTANE	Aquatic Chronic 4, H413		
INDEX: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 ETHANEDIOL	GHS07 Wng Acute Tox. 4, H302	[1]	
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE	GHS05, GHS07, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1		0 >= x % < 0.02

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9 1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1: H317 C>= 0.05%	

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with soft and clean water during 15 minutes while keeping the eyes wide opened.

Refer the subject to an ophthalmologist, especially if there is redness, pain or visual discomfort.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

Wash with water and soap. if any sign/symptom develops seek for medical assistance.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.



WOODGUARD PROFESSIONNAL - 5201

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Storage temperature : between 5 and 25°C.

Do not store closed to acids.

keep away from direct solar light.

Maximum storage : 12 months.



WOODGUARD PROFESSIONNAL - 5201

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m ³	VME-ppm	VLE-mg/m ³	VLE-ppm	Notes
107-21-1	52	20	104	40	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1	-	-	100	-	-

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
107-21-1		10 ppm 26 mg/m ³		2(I)

- France (INRS - ED984 / 2020-1546) :

CAS	VME-ppm :	VME-mg/m ³	VLE-ppm :	VLE-mg/m ³	Notes :	TMP No :
107-21-1	20	52	40	104	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
107-21-1	20 ppm 52 mg/m ³	40 ppm 104 mg/m ³		Sk	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

A MIXTURE OF:

BIS(2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-1,10-DECANEDIOATE;1,8-BIS[(2,2,6,6-TETRAMETHYL-4-((2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-DECAN-1,10-DIOYL)PIPERIDIN-1-YL)OXY]OCTANE

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Final use:

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
1.9 mg/kg body weight/day

Inhalation.
Long term systemic effects.
5.3 mg of substance/m³

Consumers.

Ingestion.
Long term systemic effects.
0.9 mg/kg body weight/day

Dermal contact.
Long term systemic effects.
0.9 mg/kg body weight/day

Inhalation.
Long term systemic effects.
1.3 mg of substance/m³

WOODGUARD PROFESSIONNAL - 5201

Predicted no effect concentration (PNEC):

A MIXTURE OF:

BIS(2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-1,10-DECANEDIOATE;1,8-BIS[(2,2,6,6-TETRAMETHYL-4-((2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-DECAN-1,10-DIOYL)PIPERIDIN-1-YL)OXY]OCTANE

Environmental compartment: PNEC :	Soil. 9170000 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.046 mg/l
Environmental compartment: PNEC :	Sea water. 0.046 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.046 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 46000000 mg/kg
Environmental compartment: PNEC :	Marine sediment. 46000000 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 1 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)

- Body protection

WOODGUARD PROFESSIONNAL - 5201

Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Fluid liquid.

Colour

Milky white

Odour

Odour threshold : Not stated.

Melting point

Melting point/melting range : Not specified.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not specified.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash point interval : Not relevant.

Auto-ignition temperature

Self-ignition temperature : 189 °C.

Decomposition temperature

Decomposition point/decomposition range : Not specified.

pH

pH : 9.00 +/-0.5.
Slightly basic.

pH (aqueous solution) : Not stated.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Soluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Not relevant.

Density and/or relative density

Density : = 1

Relative vapour density

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.



WOODGUARD PROFESSIONNAL - 5201

9.2.2. Other safety characteristics

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
 - carbon dioxide (CO₂)
-

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No data available.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

A MIXTURE OF:

BIS(2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-1,10-DECANEDIOATE;1,8-BIS[(2,2,6,6-TETRAMETHYL-4-((2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-DECAN-1,10-DIOYL)PIPERIDIN-1-YL)OXY]OCTANE

Fish toxicity :

LC50 = 58 mg/l

Duration of exposure : 96 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

A MIXTURE OF:

BIS(2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-1,10-DECANEDIOATE;1,8-BIS[(2,2,6,6-TETRAMETHYL-4-((2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-DECAN-1,10-DIOYL)PIPERIDIN-1-YL)OXY]OCTANE

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.



WOODGUARD PROFESSIONNAL - 5201

12.3. Bioaccumulative potential

12.3.1. Substances

A MIXTURE OF:

BIS(2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-1,10-DECANEDIOATE;1,8-BIS[(2,2,6,6-TETRAMETHYL-4-((2,2,6,6-TETRAMETHYL-1-OCTYLOXYPIPERI-DIN-4-YL)-DECAN-1,10-DIOYL)PIPERIDIN-1-YL)OXY]OCTANE

Octanol/water partition coefficient : log K_{ow} = 1.45

Bioaccumulation : BCF = 45

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

-

WOODGUARD PROFESSIONNAL - 5201

14.6. Special precautions for user

-

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

No data available.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H413	May cause long lasting harmful effects to aquatic life.

Abbreviations :

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.



SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
Version : N°1 (23/12/2021)
GUARD INDUSTRIE S.A.S.

Date : 03/04/2022 Page 10/10
Revision : N°9 (23/12/2021)

WOODGUARD PROFESSIONNAL - 5201

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.