

GUARD REMOVER®

Painted Surfaces



MULTIPURPOSE PAINT STRIPPER

- ✓ **ELIMINATES PAINTS, VARNISHES, PLASTIC AND ORGANIC COATINGS**
- ✓ **CAN BE USED ON A WIDE VARIETY OF SUBSTRATES**
- ✓ **LOW ODOR**
- ✓ **DOES NOT ALTER THE MATERIALS**
- ✓ **NON-HARMFUL, NON-TOXIC AND NON-FLAMMABLE**
- ✓ **INTERIOR AND EXTERIOR**

DESCRIPTION

Guard Remover® **Painted Surfaces** is a stripper designed for the removal of paints, varnishes and organic or synthetic coatings on a wide variety of surfaces.

In the form of a pasty cream, **Guard Remover® Painted Surfaces** is particularly recommended for stripping vertical surfaces without risk of dripping. Moreover, its wetting power allows a very good penetration of the support to be stripped and thus allows a better effectiveness. Because it contains no paraffin, the stripped surface can be cleaned by simply scraping it off, without rinsing, and then covered with a new coat of paint or coating.

USE

Guard Remover® **Painted Surfaces** can be used on a wide variety of substrates: concrete, stone, plaster, wood and metal.

Ideal for stripping indoor and outdoor paints, varnishes, plastic and organic coatings (acrylic, glycerine, single-component polyurethane, etc.).

BENEFITS AND FEATURES

- Non-flammable and non-toxic.
- Paraffin-free.
- Ready to use and easy to apply.
- Low odor, suitable for indoor and outdoor use.
- No rinsing required.
- Does not alter the surface.
- Versatile: multi-supports.

PACKAGING

25 kilos buckets.

TECHNICAL DATA

Physical state at 20 °C	: Paste
Color	: Beige
Smell	: Characteristic
pH	: NC
Density	: 1.4 ± 0.03
Solubility in water [vol/vol]	: Insoluble
Flash point [°C]	: 84°C

APPLICATION

- In view of the immense diversity of existing coatings, it is essential to carry out preliminary tests, particularly on very specific coatings.
- Use the product in its pure state.
- Apply a thick and regular layer of product on the support to be stripped.
- Leave the product to act until the coating has softened completely, for one to several hours depending on the type of paint and the number of coats to be removed. It is possible to let the product work overnight and strip the next morning.

Indicative action times:

- Thin film paints: 1h to 4h.
- I1 / I2 waterproof coating : 4h to 8h
- I3/I4 waterproof coating: 12 to 24 hours
- Remove residues by scraping with a scraper or a painter's knife or by cleaning with a high pressure cleaner. For use on plaster, it is not necessary to rinse.
- Stripped surfaces can be recoated with a new coat of paint or other coating after 24 hours of drying.

APPLICATION TOOLS

Apply with a roller, natural fibre brush or spatula.



CONSUMPTION

The values below are given as an indication :

1 to 3 m² / Kg.

EQUIPMENT CLEANING

Clean tools and equipment with water immediately after use.

STORAGE

- Store in a dry place at a temperature between 5°C and 30°C.
- Shelf life : 24 months from the date of manufacture, in original unopened packaging.

RECOMMENDATIONS

- For a perfect application, use imperatively when the temperature of the supports is included between 5°C and 30°C.
- Do not apply in rainy or very hot weather. Air temperature between 5°C and 30°C.
- Do not dilute or mix with other products.

HEALTH / SAFETY

- Respiratory protection: No respiratory protective equipment is required under normal conditions of use.
- Hand protection: Wear chemical resistant gloves (neoprene, PVC...).
- Skin protection: Wear long-sleeved skin protection clothing.
- Eye protection: Wear safety glasses.
- If swallowed: Do not induce vomiting. Contact a doctor or a specialist.

PRODUCT FOR PROFESSIONAL USE

TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE

Tel: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 15/01/2024