

GRAFFIGUARD® 2010



GRAFFITI CLEANER FOR REMOVING RESIDUAL GHOSTS AND OUTLINES

- ✓ REMOVES INK GHOSTS AND RESIDUES
- ✓ READY TO USE

- ✓ EASY TO USE
- ✓ DOES NOT DAMAGE MATERIALS

PRODUCT DESCRIPTION

GraffiGuard® 2010 is a cleaner that removes ink and paint stains and residues sometimes left after graffiti has been cleaned off by GraffiGuard® 2030 Ecological.

USE

GraffiGuard® 2010 is for outdoor application to porous and low porous surfaces. It is particularly recommended for surfaces with poor resistance to acids, such as rendering, sandstone and terracotta.

CHEMICAL NATURE

- A mixture of hydroxylated solvents and potassium hydroxide.

ADVANTAGES AND CHARACTERISTICS

- Removes graffiti ghosts and outlines.
- Aqueous-phase product.
- Nonflammable.
- Easy to use.
- Exterior.

CONTAINERS

2 litres.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Appearance	: Amber
Odour	: Solvent
pH	: 14 ± 1
Boiling point [°C]	: Non measured
Density	: 1.15 ± 0.02
Solubility in water [vol/vol]	: Total
Flash point [°C]	: Not applicable

HOW TO USE

- Apply neat, do not dilute.
- Shake the product well before use.
- **Always carry out a preliminary test.**
- For optimum results wet the surface before applying GraffiGuard® 2010.
- Apply GraffiGuard® 2010 with a brush, then work over the surface with circular movements.
- Leave to act for around 2 to 10 minutes.
- Rinse off with copious amounts of low-pressure water as hot as possible (increase the pressure of the pressure washer).
- Always thoroughly wet the surface beneath with water.
- Repeat entire operation if necessary.
- Rinse off with copious amounts of cold water to neutralise.

APPLICATION TOOLS

- Apply using a brush.



COVERAGE

The following values are for guidance only:

3 to 5 m² / litre

CLEANING YOUR EQUIPMENT

- Clean tools and equipment immediately after use with water.

STORAGE

- Keep in a dry place (between 5°C and 30°C).
- Storage: 48 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

- **GraffiGuard® 2010** is a corrosive product. Skin contact with the product can cause burns. Wear rubber gloves, protective clothing and goggles.
- Use with care on painted surfaces. Clean immediately after application.
- Attacks zinc, aluminium and their alloys.
- Do not apply in rain or very hot weather. Temperature of air and substrates between 5°C and 30°C.
- Do not dilute or mix with another product.

HEALTH AND SAFETY

- Respiratory protection : Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.
- Hand protection : Wear latex gloves.
- Skin protection : Wear protection clothing for the skin with long sleeves and resistant to solvents.
- Eye protection : Wear protective goggles.
- If swallowed : Do not induce vomiting. Contact a doctor or a specialist.

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD INDUSTRY

7 rue Gutenberg • 93108 MONTREUIL Cedex • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax: +33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 10/02/2020