



## POWERFUL FAST-ACTING CLEANER REMOVES BLACK SOILING AND ORGANIC STAINS

- SELF-CLEANING CONCENTRATED IN ACTIVE AGENT
- REMOVES SOILING AND RENOVATES IN 30 MINUTES

- DOES NOT ALTER THE SURFACE
- FLOORS, FACADES AND ROOFS
- STONE, CONCRETE, RENDER, TERRACOTTA, TILING

### DESCRIPTION

Guard Wash® *Express* is a concentrated product with powerful active materials enabling instant and deep cleaning of dirt invading building materials (dirt associated with damp, atmospheric pollution, traces of leaves, etc.).

The self-cleaning, quick and powerful action of Guard Wash® *Express* cleans contaminated surfaces. The original appearance of materials is restored in less than an hour with no deterioration to their colour or their mechanical properties.

Guard Wash® *Express* is also the ideal product to remove grey discolouration from wood.

### USE

Guard Wash® *Express* is an ideal universal product to treat external walls, facades, weather boarding, roofs, balconies, fountains, pools, monuments, fences, terraces, garden paving, paving, tennis courts, etc. It can be used on all materials like concrete, fibre cement, natural or reconstituted stone, terracotta, tiling, PVC, wood, etc. Particularly recommended for renders (even painted) and all types of coatings.

### ADVANTAGES AND CHARACTERISTICS

- Instant and ultra-fast action in 1 application.
- Deep cleaning without mandatory rinsing.
- Can be used on a wide range of materials.
- Does not damage mineral materials, even glass.
- Low odour and long-term storage.
- Ultra concentrated formula = effective and fast.
- Ready to use: quick and easy to use.



## CHEMICAL NATURE

- Mixture of bleaching agents and surfactants.

## CONTAINERS

- 5 and 20 litres cans.

## TECHNICAL DATA

Physical state at 20°C	: Liquid
Colour	: Light yellow
Odour	: Floral
pH	: > 13
Boiling point [°C]	: 100 °C
Density	: 1.16 ± 0.02
Water solubility [vol/vol]	: Total
Flash point [°C]	: Not applicable
COV	: < 1 g/l

## APPLICATION

- Ready to use product.
- Always test on the material before application.
- Spray onto dry or slightly damp material.

### Dilution recommendations:

- **Dirty surface+** = 1 layer.
- **Very dirty surface++** = 2 layers.  
Interval between each layer: 30 minutes.
- Let the product act for 30 to 45 minutes according to the level of soiling.
- Rinse the surface with a jet of water or high-pressure washer (60 bars maximum).
- Before repainting or applying a protective product, the material must be completely rinsed off and dry (refer to the finishing product sheet).

## APPLICATION TOOLS

- Apply using a garden-type low-pressure sprayer.



## COVERAGE

The following values are given for information:

**3 to 6 m<sup>2</sup> / litre.**

## TREATMENT / PREVENTION

### Treatment:

- To eliminate micro-organisms, perform a curative treatment with **Guard® Cleaner Algae** one day after applying **Guard Wash® Express**.

### Prevention:

- To prevent fouling again and permanently protect the surface after cleaning and drying, it is recommended to apply a preventative treatment with a product from the **ProtectGuard®** or **ImperGuard®** range.

## CLEANING OF EQUIPMENT

- Clean the tools and equipment used with water immediately after use.

## STORAGE

- Store in its original packaging in a dry place away from direct sunlight at a temperature of between 5°C and 25°C.
- Storage: 12 months from date of manufacture, in original packaging unopened.

## RECOMMENDATIONS

- For perfect application and effective action, **Guard Wash® Express** must be used when the temperature of the elements is between 5°C and 25°C.
- Do not apply if it is raining or if there is a risk of rain. If the weather is extremely hot, apply during the cooler hours of the day. Air temperature between 5°C and 25°C.
- Do not apply on metals, light alloys, fragile materials or vegetation. Always protect these materials. Rinse off any product splashes quickly with water. Avoid unnecessary splashes on areas not being treated (risk of alterations) and on clothes.
- Do not mix with another product (risk of toxic gas being released).
- Protecting vegetation: rinse any splashes of the product on plants in order to prevent any damage.
- Protecting the environment and packaging: Rinse the package with fresh water and dispose of in the plastics bin at the recycling centre. Never throw a dirty package out into the environment.

## HEALTH AND SAFETY

- Respiratory protection : No breathing equipment is required under normal conditions of use provided there is adequate ventilation. Do not inhale gases, vapours or aerosols.
- Hand protection: Wear sealed nitrile rubber gloves (EN 374-1:2003).
- Skin protection : Protective clothing (protection and apron) boots.
- Eye protection: Wear protective goggles complying with standard NF EN166.
- If swallowed: Do not induce vomiting. Contact a doctor or specialist.

**KEEP OUT OF REACH OF CHILDREN**

## TECHNICAL SUPPORT

### GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere  
31750 ESCALQUENS • FRANCE

Tel: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : [contactus@guardindustry.com](mailto:contactus@guardindustry.com)

[www.guardindustry.com](http://www.guardindustry.com)

**Important:** The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

**For the most recent version of our data sheet, visit our website**

[www.guardindustry.com](http://www.guardindustry.com)

Last updated : 09/05/2023