

PROTECTGUARD®



WATER AND OIL REPELLENT, ANTI-STAINING AND ANTI-GRAFFITI TOTAL PROTECTION FOR ALL POROUS BUILDING SUBSTRATES

- ✓ **PROTECTS AGAINST WATER, STAINING AND OIL**
- ✓ **WALLS, FLOORS AND ROOFS**
- ✓ **NON FILM-FORMING: LETS A SURFACE BREATHE**

- ✓ **ODOURLESS & CLEAR: DOES NOT CHANGE A MATERIAL'S COLOUR**
- ✓ **UV AND FROST-RESISTANT**
- ✓ **INTERIOR AND EXTERIOR**

PRODUCT DESCRIPTION

ProtectGuard® is the leading product for all-round protection for all porous building materials. This one product delivers water and oil repellent protection and anti-graffiti protection for porous building materials.

ProtectGuard® helps tackle the deterioration caused by atmospheric pollution, grease-type staining, penetration of liquids and graffiti. A surface treated with ProtectGuard® will benefit from an increased life-span and will be easier to maintain.

ProtectGuard® is a non film-forming impregnation product that leaves the treated surface permeable to air and water vapour.

ProtectGuard® is completely colourless after application and does not change the appearance or the composition of the treated surface. It is also UV-resistant and does not discolor with age.

USE

ProtectGuard® may be used indoors or outside on walls, floors and roofing. It is designed to protect all porous building materials such as natural and synthetic stone, concrete, terracotta, cement, self-locking paving...

On low porous materials, use ProtectGuard® HD or ProtectGuard® MG Eco. ProtectGuard® is used for new and renovated constructions.

CHEMICAL NATURE

- Water-borne fluorinated copolymer based.


ADVANTAGES AND CHARACTERISTICS

- Effective for more than 10 years demonstrated by the CEBTP (Experimental Centre for Research and Study in Construction and Public Works).
- Protects against water, oily liquids and staining.
- Limits efflorescence formation.
- Anti-staining, anti-dirt.
- Prevents chewing-gum from sticking, limits dirt due to pollution from building up again. Limits moss and lichen growth.
- Makes cleaning easier.
- Very good anti-graffiti properties.
- Prevents deterioration resulting from freeze-thaw cycle.
- Non film-forming, lets the surface breathe.
- UV-resistant, does not discolor.
- Invisible once dry.
- Ready to use, easy to use.

ENVIRONMENT

Environment-friendly product:

- Water-based product.
- Petroleum solvent and silicone free.
- Non hazardous and non toxic.
- 100% biodegradable*.
- VOC < 2 g/l*.
- 2008 Award of the "Éco Trophées 93"



A 10 Year Quality

*For more information consult us



CONTAINERS

2, 5, 10 and 25 litres.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Appearance	: Uncoloured
Odour	: None
pH	: 5.5 ± 0.5
Boiling point [°C]	: 100 °C
Density	: 1.0 ± 0.01
Solubility in water [vol/vol]	: Total
Flash point [°C]	: Not applicable

HOW TO USE

Surface preparation :

- Apply the product to a surface that is clean, dust-free, grease-free and dry. To remove stains and marks of pollution use **Guard Cleaner® Polluted Facades**. In case of greasy stains use **Guard Cleaner® Eco Soiled Floors**. For efflorescence, laitance or concrete bloom use **Guard Remover® Eco Efflorescence & Cement**.
- Rinse carefully and wait until the surface is completely free from any cleaner marks before applying **ProtectGuard®**.

Application :

- Use neat, do not dilute.
- Shake the product well before use.
- Always carry out a preliminary test.
- The treated surface should be impregnated to saturation point, either in one application or in two applications 'wet-on-wet'.
- **Do not over apply, eliminate any exceeding product before drying.**
- On vertical surfaces, apply from the bottom-up.
- Drying time: 24 hours.
- Optimum effectiveness obtained after 7 days.

APPLICATION TOOLS

- Apply using a low pressure sprayer, a roller or a brush.



MAINTENANCE

- Stubborn dirt should be cleaned off with clean water or with a pH neutral cleaner.

COVERAGE

Coverage depends on the porosity of the material. The figures below should be used only as a general guideline:

Terracotta	7.00 m ² /l
Concrete	5.00 m ² /l
Floor tiles	5.00 m ² /l
Interlocking pavement	4.00 m ² /l
Stone cladding	4.00 m ² /l
MPC type layer	2.50 m ² /l
Limestone	2.00 m ² /l
Freestone	1.30 m ² /l
St Vaast-type stone	0.60 m ² /l

* Calculation based on the components' data.

CLEANING YOUR EQUIPMENT

- Clean tools and equipment immediately after use with water.

STORAGE

- Keep in a dry place (between 5°C and 30°C).
- Storage: 24 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

- Remove all atmospheric pollution-related dirt from all surfaces to be treated before starting the treatment.
- For best results it is essential that **ProtectGuard®** is used when the temperature of the substrates is between 5°C and 30°C.
- Do not apply to low or very low porous materials (in this case use **ProtectGuard® HD** or **ProtectGuard® MG Eco**).
- Do not apply to organic, metallic or waterproofing materials.
- Do not apply during rain or in very hot weather. Air temperature between 5°C and 30°C.
- Do not dilute or mix with any other product.
- We recommend maintaining regularly the surface to keep its new look.
- **ProtectGuard®** does not prevent from tire marks on floors. To remove these marks, use **Guard Cleaner® Eco Soiled Floors**.
- Some stains (eg. stains from leaves) seem harder to remove. In this case, just apply some **Guard Wash®**, let it act and then rinse with water. It will not remove the protection product.

HEALTH AND SAFETY

- **Respiratory protection** : Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.
- **Hand protection** : Wear latex gloves.
- **Skin protection** : No special protective clothing or skin protection is required under normal conditions of use.
- **Eye protection** : If there is a real risk of splashing, wear protective goggles.
- **If swallowed** : Do not induce vomiting. Contact a doctor or a specialist.

KEEP OUT OF THE REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD INDUSTRY

7 rue Gutenberg • 93108 MONTREUIL Cedex • FRANCE
Tél: +33 (0)1.55.86.17.60 • Fax: +33 (0)1.48.58.16.89
E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 01/02/2016