

Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Revision: N°10 (07/06/2022)

Date: 18/05/2023 Page 1/12

GUARD REMOVER GRAFFITI 2010 - 1210

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: GUARD REMOVER GRAFFITI 2010

Product code: 1210.

UFI: 2VA3-303P-A00A-K9H8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Graffiti Remover Porous mineral substrates

1.3. Details of the supplier of the safety data sheet

Registered company name: GUARD INDUSTRIE S.A.S.. Address: 7 Rue Gutenberg.93100.Montreuil.France. Telephone: 0155861760. Fax: 0148581689.

info@guardindustrie.com www.guardindustrie.com

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:



GHS05

 $Signal\ Word:$

DANGER

Product identifiers:

019-002-00-8 POTASSIUM HYDROXIDE EC 259-217-6 HEXYL-D-GLUCOSIDE

CAS 68439-46-3 ALCOHOLS, C9-C11, ETHOXYLATED

 $Hazard\ statements:$

H314 Causes severe skin burns and eye damage.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Date: 18/05/2023 Page 2/12 Revision: N°10 (07/06/2022)

GUARD REMOVER GRAFFITI 2010 - 1210

Precautionary statements - Prevention:

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or a doctor.
P321 In case of visiting a doctor, show the MSDS.
P363 Wash contaminated clothing before reuse.

Precautionary statements - Storage:

P405 Store locked up.

Precautionary statements - Disposal :

P501 Dispose of contents/container to a centre for harmful waste.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Identification	(EC) 1272/2008	Note	%
CAS: 111-90-0	GHS07	[1]	50 <= x % < 100
EC: 203-919-7	Wng		
	Eye Irrit. 2, H319		
2-(ETHOXYETHOXY)ETHANOL			
INDEX: 019-002-00-8	GHS05, GHS07	[1]	10 <= x % < 25
CAS: 1310-58-3	Dgr		
EC: 215-181-3	Acute Tox. 4, H302		
	Skin Corr. 1A, H314		
POTASSIUM HYDROXIDE			
INDEX: 603-014-00-0	GHS07	[1]	2.5 <= x % < 10
CAS: 111-76-2	Wng		
EC: 203-905-0	Acute Tox. 4, H332		
	Acute Tox. 4, H302		
2-BUTOXYETHANOL	Skin Irrit. 2, H315		
	Eye Irrit. 2, H319		
CAS: 54549-24-5	GHS05		2.5 <= x % < 10
EC: 259-217-6	Dgr		
REACH: 01-2119492545-29-29	Eye Dam. 1, H318		
HEXYL-D-GLUCOSIDE			
CAS: 68439-46-3	GHS05		2.5 <= x % < 10
	Dgr		
ALCOHOLS, C9-C11, ETHOXYLATED	Eye Dam. 1, H318		



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Date: 18/05/2023 Page 3/12 Revision: N°10 (07/06/2022)

GUARD REMOVER GRAFFITI 2010 - 1210

Specific concentration limits:

Specific concentration mines		
Identification	Specific concentration limits	ATE
INDEX: 019-002-00-8	Skin Corr. 1A: H314 C>= 5%	
CAS: 1310-58-3	Skin Corr. 1B: H314 2% <= C < 5%	
EC: 215-181-3	Skin Irrit. 2: H315 0.5% <= C < 2%	
	Eye Dam. 1: H318 C>= 2%	
POTASSIUM HYDROXIDE	Eye Irrit. 2: H319 0.5% <= C < 2%	
INDEX: 603-014-00-0		oral: ATE = 1200 mg/kg BW
CAS: 111-76-2		
EC: 203-905-0		
2-BUTOXYETHANOL		

Information on ingredients:

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures

In the event of exposure by inhalation:

Take immediately the victim to fresh air. if breathing is difficult, call a doctor immediately.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin:

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated aera is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Wash immediately and thoroughly with water.

Wash with water and soap. if any sign/symptom develops seek for medical assistance.

In the event of swallowing:

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S.

GUARD REMOVER GRAFFITI 2010 - 1210

Date: 18/05/2023 Page 4/12

Revision: N°10 (07/06/2022)

5.3. Advice for firefighters

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention:

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Storage temperature : between 5 and $25^{\circ}\text{C}.$

Do not store closed to acids. keep away from direct solar light. Max. storage time: 24 months

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Revision : N°10 (07/06/2022)

Date: 18/05/2023 Page 5/12

GUARD REMOVER GRAFFITI 2010 - 1210

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:
111-76-2	98	20	246	50	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
1310-58-3			2 mg/m3		
111-76-2	20 ppm			A3; BEI	

- Germany - AGW (BAuA - TRGS 900, 02/2022):

CAS	VME:	VME:	Excess	Notes
111-90-0		6 ppm		2(I)
		35 mg/m^3		
111-76-2		10 ppm		2(I)
		49 mg/m^3		

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
1310-58-3	-	-	-	2	-	-
111-76-2	10	49	50	246	*	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020):

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
1310-58-3		2 mg/m³			
111-76-2	25 ppm	50 ppm		Sk. BMGV	
	123 mg/m^3	246 mg/m^3			

HEXYL-D-GLUCOSIDE (CAS: 54549-24-5)

Final use: Workers.
Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 595000 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.
DNEL: 420 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 35.7 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 357000 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 124 mg of substance/m3



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Revision: N°10 (07/06/2022)

Date: 18/05/2023 Page 6/12

GUARD REMOVER GRAFFITI 2010 - 1210

Predicted no effect concentration (PNEC):

HEXYL-D-GLUCOSIDE (CAS: 54549-24-5)

Environmental compartment: Soil.

PNEC: 0.654 mg/kg

Environmental compartment: Fresh water. PNEC: 0.176 mg/l

Environmental compartment: Sea water. PNEC: 0.018 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 0.722 mg/kg

Environmental compartment: Marine sediment. PNEC: 0.072 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 100 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):









Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S.

Date: 18/05/2023 Page 7/12

Revision: N°10 (07/06/2022)

GUARD REMOVER GRAFFITI 2010 - 1210

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES 9.1. Information on basic physical and chemical properties

Physical state			
I IIVSICAI STATE			

Physical state: Colour

Fluid liquid.

Amber

Odour

Odour threshold: Not stated.

Caractertistic

Melting point

Melting point/melting range: Not specified.

Freezing point

Freezing point / Freezing range: Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range: Not specified.

Flammability

Flammability (solid, gas): Not stated.

Lower and upper explosion limit

Not stated. Explosive properties, lower explosivity limit (%): Explosive properties, upper explosivity limit (%): Not stated.

Flash point

Not relevant. Flash point interval:

Auto-ignition temperature

Self-ignition temperature : Not specified.

Decomposition temperature

Decomposition point/decomposition range: Not specified.

pН

14.00 +/-1. pH: Strongly basic.

Not stated.

pH (aqueous solution):

Kinematic viscosity

Viscosity: Not stated.

Solubility

Water solubility: Soluble. Not stated. Fat solubility:

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water: Not stated.



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Revision: N°10 (07/06/2022)

GUARD REMOVER GRAFFITI 2010 - 1210

Vapour pressure

Vapour pressure (50°C): Not relevant.

Density and/or relative density

Density: 1.085

Method for determining the density:

ISO 3507 (Laboratory glassware - Pycnometers).

Date: 18/05/2023 Page 8/12

Relative vapour density

Vapour density: Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

9.2.2. Other safety characteristics

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid:

- frost

10.5. Incompatible materials

Keep away from:

- acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

11.1.1. Substances

Acute toxicity:

HEXYL-D-GLUCOSIDE (CAS: 54549-24-5)

Oral route : LD50 > 2000 mg/kg

Species: Rat

Dermal route : LD50 > 2000 mg/kg

Species: Rabbit

2-BUTOXYETHANOL (CAS: 111-76-2)



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S.

GUARD REMOVER GRAFFITI 2010 - 1210

Date: 18/05/2023 Page 9/12 Revision: N°10 (07/06/2022)

Oral route : LD50 = 1200 mg/kg

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards

Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 102-71-6: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans. CAS 111-76-2: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

HEXYL-D-GLUCOSIDE (CAS: 54549-24-5)

Fish toxicity: LC50 > 100 mg/l

Duration of exposure : 96 h

Crustacean toxicity: EC50 > 100 mg/l

Species: Daphnia sp.

Duration of exposure: 48 h

Algae toxicity: ECr50 > 100 mg/l

Duration of exposure: 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

HEXYL-D-GLUCOSIDE (CAS: 54549-24-5)

Biodegradability: Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

HEXYL-D-GLUCOSIDE (CAS: 54549-24-5)

Bioaccumulation: BCF < 100.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws):

WGK 1: Slightly hazardous for water.



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S.

GUARD REMOVER GRAFFITI 2010 - 1210

Date: 18/05/2023 Page 10/12

Revision: N°10 (07/06/2022)

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste):

20 01 13 * solvents

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

14.1. UN number or ID number

1814

14.2. UN proper shipping name

UN1814=POTASSIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

П

14.5. Environmental hazards

_

14.6. Special precautions for user

ſ	ADR/RID	Class	Codo	Dools on	Labal	Idont	10	Provis	EO	Cat	Tunnal
l	ADK/KID	Class	Code	Pack gr.	Label	Ident.	LQ	PIOVIS.		Cat.	Tunnel
		8	C5	II	8	80	1 L	-	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation
								Handling	
	8	-	II	1 L	F-A. S-B	-	E2	Category A	SGG18 SG35

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	II	851	1 L	855	30 L	A3 A803	E2
	8	-	II	Y840	0.5 L	-	-	A3 A803	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S.

GUARD REMOVER GRAFFITI 2010 - 1210

Date: 18/05/2023 Page 11/12

Revision: N°10 (07/06/2022)

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/643 (ATP 16)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2021/849 (ATP 17)

- Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3). Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws):

WGK 1: Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

Abbreviations:

LD50: The dose of a test substance resulting in 50% lethality in a given time period.

LC50: The concentration of a test substance resulting in 50% lethality in a given period.

EC50: The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

REACH: Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE: Acute Toxicity Estimate

BW: Body Weight

DNEL: Derived No-Effect Level

PNEC: Predicted No-Effect Concentration

UFI: Unique formulation identifier. STEL: Short-term exposure limit TWA: Time Weighted Averages

TMP: French Occupational Illness table

TLV: Threshold Limit Value (exposure)



Version: N°1 (07/06/2022) GUARD INDUSTRIE S.A.S. Date : 18/05/2023 Page 12/12 Revision : N°10 (07/06/2022)

GUARD REMOVER GRAFFITI 2010 - 1210

AEV: Average Exposure Value.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

WGK: Wassergefahrdungsklasse (Water Hazard Class).

GHS05: Corrosion

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.