



Permanent graffiti protection, oil/water repellent for concrete. Flat or satin finish.

- Permanent anti-graffitis protection
- Protection against water, oil and staining
- Two-component, resists to 20 graffiti cleanings

SPECIFICATION TEXT

Implementation of AntiGraffiti Guard® or equivalent. The product should be a two-components product that is water-repellent, oil-repellent, stain-resistant and anti-graffitis. It should be formulated with a water-borne polyurethane. It should allow the substrate to breathe up to 90% . A clear primer like Primer Guard® or a coloured primer like Primer Guard® Color should be applied first according to the manufacturer's recommendations.
Satin or flat finish.

TESTS

- Water-repellency (LRVision)
- Oil resistance (LRVision)
- Abrasion resistance (LRVision)
- UV resistance (LRVision)
- Water absorption (LRVision)
- Fire test (Crepim)
- Chloride resistance (LMDC)

APPLICATION

Implementation according to the manufacturer's recommendations and technical information sheet. Work carried out by a trained and approved company will benefit from a 5-year AXA contractual guarantee of good performance.

Substrate preparation :

- The conditions of application and preparation of substrates comply with DTU 59.1.
- Removal of efflorescence and cement residue with Guard Cleaner® Eco Surface Preparation or equivalent.
- Removal of existing paint with Guard Remover® Eco VG Painted Surfaces or equivalent.
- Removal of organic soiling with Guard Wash® Express or equivalent.
- Removal of greasy stains and residues of form oil with Guard Cleaner® Eco Maintenance or equivalent.

Application with HVLP or roller in 2 to 4 layers according to the desired finish. See technical data sheet.