



Water and oil repellent  
stain for GRP.  
Standard shades

- Semi-transparent stain
- Two-components product
- 42 standard shades, custom-made shades
- Protects against water, stains and graffiti

### SPECIFICATION TEXT

Implementation of ProtectGuard® Color Special GRP or equivalent. The product should be a two-component coloured glaze that is water-repellent, oil-repellent, stain-resistant and anti-graffiti. It should be formulated with an acrylic resin and water-borne fluorinated acrylic copolymer with UV-stable mineral pigments. It should allow the substrate to breathe up to 90%.

Product should not deteriorate the fire performances of concrete.

Opacity and colours to be validated by the architect, according to the manufacturer's standard colour chart, RAL reference or other colour charts.

### TESTS

- Performance test (LRVision)
- Fire test (Thomas Bell)

### APPLICATION

Implementation according to the manufacturer's recommendations and technical information sheet. Work carried out by a trained and approved company will benefit from a 10-year AXA contractual guarantee of good performance.

#### Substrate preparation :

- The conditions of application and preparation of substrates comply with DTU 59.1.
- Removal of organic soiling with Guard Wash® Express or equivalent.
- Removal of greasy stains and residues of form oil with Guard Cleaner® Eco Maintenance or equivalent.

**Application with an air-assisted spray gun or brush in 2 layers according to the desired finish. See technical data sheet.**