


GUARD TECH CLEANER®





BIODEGRADABLE RUST REMOVER FOR RMC PLANT EQUIPMENT

POWERFUL STRIPPER

FAST ACTION

MON-CORROSIVE & NON-NOCIVE

BIODEGRADABLE

SAFE & READY TO USE

PRODUCT DESCRIPTION

GTC® is a rust stripper to designed for cleaning formwork and all materials used in building and civil engineering.

GTC® has been designed to meet the various requirements of applicators — safety of use, effectiveness, low environmental impact and respect for the surfaces treated. Unlike conventional acid products it is not classified as corrosive, meaning it poses much less of a hazard during use.

USE

GTC® is for outdoor use for removing rust from formwork and all building and civil engineering materials.

CHEMICAL NATURE

Formulation based on organic compounds.

ADVANTAGES AND CHARACTERISTICS

- 70% biodegradable after 28 days.
- No risk to the environment.
- Powerful fast-acting stripper.
- Non corrosive.
- Easy and quick to use.
- Ready to use.

CONTAINERS

25 Kg containers.230 Kg drums.1000 Kg IBC containers.







APPLICATION TOOLS

Apply with a low-pressure sprayer.



TECHNICAL DATA

Physical state at 20 °C : Viscous liquid Colour : Uncoloured Odour : Lemon PH : < 2 Relative density : 1.13 ± 0.01

Solubility in water [vol/vol] : Total

Flashpoint [°C] : Not applicable

VOCs $: < I g/I^*$

HOW TO USE

- It is essential to do tests first.
- Shake the product well before use.
- Spray the product with a low-pressure sprayer onto the dry substrate.
- Leave the product to act for about 30 minutes.
 This time will vary depending on the amount of rust to be removed.
- Rinse the entire surface thoroughly, preferably with a high pressure cleaner.
- Scrape the surface to remove water and promote rapid drying.

PREVENTION

To avoid reoxidation and the reappearance of rust after cleaning and drying the equipment, it is recommended to carry out a preventive treatment with the protective product from the VG Max[®].

COVERAGE

The following values are for guidance only:

8 to 10 m²/ kg.

CLEANING YOUR EQUIPMENT

Tools and equipment should be cleaned with water immediately after use.

STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C.
- Shelf-life: 24 months from date of manufacture, in original unopened can.

RECOMMENDATIONS

- Wear protective gloves, clothes and goggles.
- Do not allow product to dry.
- Do not dilute or mix with another product.
- For best results it is essential that, GTC® be used when the temperature of the substrates is between 5°C and 30°C.
- Do not apply in rain or very hot weather. Air temperature between 5°C and 30°C.

HEALTH AND SAFETY

- Breathing protection: No breathing protection equipment is required under normal use conditions.
- <u>Hand protection</u>: Wear chemical-resistant gloves (neoprene, PVC or similar).
- <u>Skin protection:</u> Wear clothes that will protect the skin and have long sleeves.
- Eye protection: Wear protective goggles.
- In case of ingestion: Do not induce vomiting.
 Contact a doctor or specialist.

FOR PROFESSIONAL USE ONLY







TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere 31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail: contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated: 23/03/2023