

# GUARDTECH NEUTRALIZER®



## NON STICK PROTECTIVE AND CLEANING OIL FOR CONCRETE MIXERS

- ✓ PREVENTS CONCRETE FROM STICKING
- ✓ DISSOLVES CONCRETE AND MORTAR RESIDUES
- ✓ NON-CORROSIVE & NON-IRRITANT

- ✓ SAFE & READY TO USE
- ✓ BASED ON RECYCLED PLANT MATERIALS
- ✓ BIODEGRADABLE

### PRODUCT DESCRIPTION


GTN® is a release agent to protect machinery from concrete.

GTN® softens concrete residues that accumulate over the course of a working day. It is designed to be used on a daily basis. At the end of a working day reducing concrete residues during the night.

Thanks to its protection properties, GTN® prevents concrete from contaminating equipment and makes maintenance easier.

GTN® helps to increase the lifespan of machinery.

GTN® is significantly less hazardous than other products available on the market. It does not contain petrochemical-based products, heavy metals and is not corrosive. It can be applied to any material without alteration (metal, rubber, paint...).



### USE

Ideal for maintaining and protecting: concrete mixers, concrete moulds...



## ADVANTAGES AND CHARACTERISTICS

- Enhanced operator safety profile.
- Environment-friendly.
- Quick and easy to use.

## CHEMICAL NATURE

Mix of 100% organic-based raw material of which 91% coming from second generation recycled oil.

## ENVIRONMENT

### Ecological and respects the environment:

- Non toxic, non corrosive, non irritant.
- PCB and CMR-free.
- VOC < 1 g/l\*.
- 100% organic-based of which 91% recycled.
- Biodegradable up to 90%\* in 28 days.

## CONTAINERS

25L containers.  
200L drums.  
1000L IBC containers.

## TECHNICAL DATA

Physical state at 20 °C	: Liquid
Colour	: Amber
Odour	: Slight
pH	: Not applicable
Viscosity at 20°C [mPa.s]	: 25
Density	: 0,93 ± 0,02
Solubility in water [vol/vol]	: Insoluble
Flashpoint [°C]	: Not applicable

## HOW TO USE

- It is essential to do tests first.
- Use the product neat: do not dilute or mix with other products.
- In certain case, an excess of product can lead to air in the concrete. Spray the product uniformly.

### CURATIVE:

- Spray the product at the end of a working day. Oil must cover the concrete to be removed.
- Wait at least 12 hours.
- Rinse preferably with a high pressure cleaner or water jet. Eliminate any oil residue before applying a new coat of product.
- Repeat the operation until concrete has totally disappeared.

### PREVENTIVE:

- Spray the product on a daily basis at the end of a working day in order to prevent concrete from sticking and increase the machinery life-span
- It is also possible to apply the product during the working day.

## APPLICATION TOOLS

Apply with a low-pressure sprayer.



## COVERAGE

Oil must be uniformly applied.  
The following values are for guidance only:

**30 to 40 m<sup>2</sup> / litre.**

## STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C.
- Shelf-life: 12 months from date of manufacture, in original unopened container.

## RECOMMENDATIONS

- For best results it is essential to use GTN® when air and surface temperature is above 0°C.
- Do not apply during rain.
- GTN® hardens below -7°C.

## HEALTH AND SAFETY

- Breathing protection: No breathing protection equipment is required under normal use conditions.
- Hand protection: Wear chemical-resistant gloves (neoprene, PVC or similar).
- Skin protection: Wear clothes that will protect the skin and have long sleeves.
- Eye protection: Wear protective goggles.
- In case of ingestion: Do not induce vomiting. Contact a doctor or specialist.

### FOR PROFESSIONAL USE ONLY



## TECHNICAL SUPPORT

### GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere

31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax: +33 (0)1.48.58.16.89

E-mail : [contactus@guardindustry.com](mailto:contactus@guardindustry.com)

[www.guardindustry.com](http://www.guardindustry.com)

**Important:** The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website  
[www.guardindustry.com](http://www.guardindustry.com)

Last updated : 23/03/2023