



GUARD TECH WASH & GO



Code: 8600



BIODEGRADABLE ACTIVE FOAM SHAMPOO FOR ALL BUILDING MATERIALS

PRODUCT DESCRIPTION

GT[®] Wash & Go is a new-generation degreasing shampoo and laitance remover developed to meet today's regulations.

GT[®] Wash & Go efficiently removes laitance, oils, grease and road film.

GT[®] Wash & Go is not classed as corrosive or irritant, which adds to its safety in use. Containing no phosphate, sodium hydroxide or potassium, it is designed to meet the needs of application personnel in terms of effectiveness, safety, ease of use and environmental impact.

USE

GT[®] Wash & Go is ideal for weekly maintenance of builder's plant, utility vehicles and heavy goods vehicles.

CHEMICAL NATURE

• Formulation based on organic compounds.

ADVANTAGES AND CHARACTERISTICS

- 70% biodegradable after 28 days.
- No risk to the environment.
- Powerful, fast-acting cleaner.
- Non-corrosive, non irritant.
- Quick and easy to use.
- Ready to use.

CONTAINERS

10 L, 220 L and 1000 L containers.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Colour	: Colourless
Odour	: Pleasant
pН	: < 3
Decomposition temperature	: > 100 °C
Relative density	: 1.06 ± 0.01
Solubility in water [vol/vol]	: Total
Flashpoint [°C]	: > 250 °C
VOCs*	:< g/l*

HOW TO USE

- It is essential to test first, and to wear personal protective equipment.
- Do not mix with other products. The product can be used neat or diluted with water (I volume of product to I volume of water).
- Spray the product evenly with a low-pressure hand sprayer. With its slightly foamy appearance, it is easy to ensure all areas of the substrate have been sprayed evenly (like painting).
- Leave to act for 5 10 minutes.
- Brush the treated surface with a medium-hard brush. The mechanical action helps removes more residues.
- Rinse the whole surface and all equipment with plenty of water, using a water jet or high-pressure cleaner. Repeat if necessary.

APPLICATION TOOLS

• Apply with a low-pressure sprayer.



COVERAGE

The following values are for guidance only:

3 to 5 m²/ L

CLEANING YOUR EQUIPMENT

 Tools and equipment should be cleaned with water immediately after use.

STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C.
- Shelf-life: 24 months from date of manufacture, in original unopened can.

RECOMMENDATIONS

- Wear protective gloves, clothes and goggles.
- Do not allow to dry.
- Do not dilute or mix with another product.
- For ideal application it is essential that GT[®] Wash & Go be used when the temperature of the substrates is between 5°C and 30°C.
- Do not apply during rain or in very hot weather. Air temperature: between 5°C and 30°C.

HEALTH AND SAFETY

- <u>Breathing protection</u>: No breathing protection equipment is required under normal use conditions.
- <u>Hand protection</u>: Wear chemical-resistant gloves (neoprene, PVC or similar).
- <u>Skin protection</u>: Wear clothes that will protect the skin and have long sleeves.
- Eye protection: Wear protective goggles.
- <u>In case of ingestion</u>: Do not induce vomiting. Contact a doctor or specialist.

KEEP OUT OF REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD INDUSTRY

7 rue Gutenberg • 93108 MONTREUIL Cedex • FRANCE Tél: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated : 05/09/2016