

GUARDTECH NEUTRALIZER®



NON-STICK PROTECTIVE MINERAL OIL FOR CONCRETE MIXERS

- ✓ LIMITS CONCRETE ADHESION
- ✓ NON-EMULSIFIABLE
- ✓ NON-CORROSIVE - NON IRRITANT

- ✓ PRESERVES MATERIALS
- ✓ BIODÉGRADABLE

DESCRIPTION

GTN® Minéral avoids the clogging of the equipment by the concrete by limiting the adhesion of the concrete or the laitance and thus facilitates the maintenance. The product increases the life of the equipment.

USE

Ideal for the protection and maintenance of construction equipment: mixers, molds, etc.

CONTAINERS

20L containers.
200L drums.
1000L IBC containers.

COVERAGE

The oil must cover the mixer.
As an indication, on average: **30 to 40 m² / litre**.

APPLICATION

- Pre-testing is essential.
- Apply the product undiluted to a clean surface.
- Use the product in its pure state: do not dilute or mix with other products.
- Apply a thin film of product uniformly, avoiding gaps and overthicknesses (do not overload the substrate).
- Clean tools and equipment with White Spirit immediately after use.

APPLICATION TOOLS

Apply with a low pressure sprayer, roller or brush.

TECHNICAL DATA

| | |
|-------------------------------|------------------|
| Physical condition at 20 °C | : Liquid |
| Color | : Brown |
| Smell | : Characteristic |
| pH | : Not applicable |
| Flash point | : > 140 °C |
| Boiling point | : > 280 °C |
| Density | : 0,86 ± 0.01 |
| Solubility in water [vol/vol] | : Insoluble |

EQUIPMENT CLEANING

Clean tools and equipment with White Spirit immediately after use.

STORAGE

- Store in a dry place at a temperature between 5°C and 30°C.
- Shelf life : 24 months from the date of manufacture, in original unopened packaging.

RECOMMENDATIONS

- Treat only surfaces that have been cleaned of air pollution and stains.
- Always carry out tests before use to ensure that the product's instructions and application conditions are satisfactory
- For perfect application and effective protection, **GTN® Minéral** should be used when the temperature of the substrates and air is between + 5°C and + 35°C.
- **GTN® Minéral** is not recommended to protect benches and site equipment.
- Do not handle in the presence of flame.
- When applying by spraying, precautions must be taken regarding aerosol formation.

HEALTH AND SAFETY

- Respiratory protection : Wear a protective mask.
- Hand protection : Wear chemical resistant gloves (neoprene, PVC...).
- Skin Protection : Wear protective clothing with long sleeves.
- Eye protection : Porter des lunettes de protection.
- En cas d'ingestion : Wear safety glasses.
- In case of ingestion: Do not induce vomiting. Contact a doctor or a specialist.

FOR PROFESSIONAL USE ONLY



TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax: +33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 23/03/2023