

GUARDTECH PROTECT®



MINERAL PROTECTIVE AGENT WITH ANTI-STICKING PROPERTIES FOR RMC PLANT EQUIPMENT

✓ **PROTECTS AGAINST CONCRETE, MORTAR AND BITUMEN PROJECTIONS**

✓ **DOES NOT BECOME STICKY**

✓ **NON-CORROSIVE / NON-IRRITANT**

✓ **BIODEGRADABLE**

DESCRIPTION

GTP® Mineral is a very effective product designed to protect equipment against concrete and mortar projections. Thanks to its protective film, the deposits will be thus easily eliminated with the water jet or the high pressure cleaner.

GTP® Mineral protects against concrete adhesion and is also embedded in existing layers. Old layers soften and can be easily removed with a spatula or high-pressure jet. All removable parts are also lubricated at the same time.

USE

Ideal for the protection of the material of the building industry: formworks, mixers, trucks, finishers, tools...

ADVANTAGES AND CHARACTERISTICS

- High performance anti-adhesive.
- Easy and quick to implement.

APPLICATION

- It is essential to carry out preliminary tests.
- Use the product in its pure state: do not dilute or mix with other products.
- Shake the can well before use.
- The support must be perfectly clean and dry.
- Apply the product evenly.
- Repeat the operation after each high pressure wash.

APPLICATION TOOLS

Apply with low pressure sprayer.

COVERAGE

The values below are given as an indication :

30 to 40 m² / litre.

CHEMICAL NATURE

Additive formulation.

TECHNICAL DATA

Physical condition at 20 °C	: Liquid
Color	: Brown
Smell	: Feature
pH	: Not applicable
Flash point	: > 140 °C
Boiling point	: > 280 °C
Density	: 0,86 ± 0.01
Solubility in water [vol/vol]	: Insoluble

PACKAGING

20L containers.
200L drums.
1000L IBC containers.

EQUIPMENT CLEANING

Clean used tools and equipment with White Spirit immediately after use.

STORAGE

- Store in a dry place at a temperature between 5°C and 30°C.
- Shelf life: 24 months from the date of manufacture, in original unopened cans.

RECOMMENDATIONS

- For a perfect application and an effective protection, **GTP® Minéral** must be used when the temperature of the supports is between 5°C and 30°C.
- Do not apply in rainy or very hot weather. Air temperature between 5°C and 30°C.

HEALTH / SAFETY

- Breathing protection : Wear a protective mask.
- Hand protection : Wear chemical resistant gloves (neoprene, PVC...).
- Skin protection : Wear long-sleeved protective clothing.
- Eye protection : Wear protective eyewear.
- In case of ingestion : Do not induce vomiting. Contact a doctor or specialist.

FOR PROFESSIONAL USE ONLY



TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax: +33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 23/03/2023