

GUARD CLEANER®

Polluted Facade

**NEW
FORMULA**



HIGH POWERFUL CLEANER REMOVES BLACKENING AND DIRT DUE TO POLLUTION

THOROUGHLY REMOVES DIRT FROM SURFACES HEAVILY SOILED BY ATMOSPHERIC POLLUTION

FAST ACTION IN 10 MINUTES
 GEL FORMULA
 IDEAL FOR BRICK, CONCRETE, HARD STONE

PRODUCT DESCRIPTION

Guard Cleaner® Polluted Facade is a product specially designed for stripping building facades heavily soiled by atmospheric pollution.

Its wetting and penetrating action is perfect for removing combustion residues and emulsifying dirt which can then be removed by rinsing.

Application and the length of time you leave the product to act should vary according to the nature and extent of soiling as well as the type and porosity of the treated surface.

ADVANTAGES AND CHARACTERISTICS

- Fast acting.
- Cleans and degreases thoroughly.
- Can be used on a wide variety of surfaces.
- Ready to use: quick and easy to use.

USE

Ideal for exterior cleaning of facades made of non-fragile mineral materials: limestone, concrete, brick, sandstone, etc.

On fragile or soft limestone, use Guard Cleaner® Stone.

On render finish preferably apply Guard Wash® Express.

CONTAINERS

25L buckets.



TECHNICAL DATA

Physical state at 20 °C	: Viscous liquid
Appearance	: White
Odour	: Characteristic
pH	: 2 ± 0.5
Boiling point [°C]	: Not applicable
Density	: 1.03 ± 0.05
Solubility in water [vol/vol]	: Total
Flash point [°C]	: Not applicable

HOW TO USE

- Ready to use product; apply neat.
- Carry out a preliminary test on a small hidden portion of the substrate.
- Wet the surface with water beforehand.
- Apply the product liberally from the bottom to the top of the surface.
- Allow it to act from 15 to 60 minutes depending on the level of soiling.
- Do not let the product dry.
- Rinse the surface with a high pressure cleaner, with hot water for more efficiency
- If necessary, repeat the operation on heavily soiled areas.

APPLICATION TOOLS

Apply with a roller or a brush.



PREVENTION

To prevent future soiling, it is recommended to protect the surface with a protection treatment from the ImperGuard® or ProtectGuard® range.

COVERAGE

The following values are for guidance only:

2 to 3 m² / L.

CLEANING YOUR EQUIPMENT

Tools and equipment should be cleaned with water immediately after use.

STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C.
- Shelf-life: 48 months from date of manufacture, in original unopened can.

RECOMMENDATIONS

- **Guard Cleaner® Polluted Facade** is an acid product, contact with the skin may cause burns. Wear protective gloves, clothing and goggles.
- Protect openings, attack aluminium, zinc, tin, lead, copper and glass.
- Always carry out a test beforehand to check compatibility.
- For best results it is essential that product is used when the temperature of the substrates is between 5°C and 30°C.
- Do not apply during rain or in very hot weather. Air temperature between 5°C and 30°C.

HEALTH AND SAFETY

- Breathing protection: No breathing protection equipment is required under normal use conditions with suitable ventilation.
- Hand protection: Wear suitable protective gloves (EN 374-1:2003).
- Skin protection: Wear waterproof protective clothing.
- Eye protection: Wear protective goggles in accordance with NF EN166.
- In case of ingestion: Do not induce vomiting. Contact a doctor or specialist.

PRODUCT FOR PROFESSIONAL USE

TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE

Tel: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated : 25/05/2023