

IMPERGUARD®

EXPRESS



TRANSPARENT SEALER FOR SPECIAL FRESH OR YOUNG CONCRETE WATER-REPELLENT & ANTI-EFFLORESCENCE

- ✓ CAN BE USED 24 HOURS AFTER DEMOULDING
- ✓ PROTECTS AGAINST WATER AND EFFLORESCENCE
- ✓ FACADE, FLOOR & ROOF
- ✓ INTERIOR & EXTERIOR
- ✓ ALLOWS SUBSTRATE TO BREATHE & UV-RESISTANT
- ✓ IDEAL FOR THE CONCRETE INDUSTRY

DESCRIPTION

ImperGuard® *Express* is a product designed to protect porous or low-porous facades and floors made of young alkaline concrete against water and rising efflorescence. ImperGuard® *Express* retards the deterioration of treated surfaces and simplifies their maintenance.

By its specific composition, ImperGuard® *Express* can be applied on hardened concrete 24 hours after its implementation on site or after demoulding in a prefabrication plant.


ImperGuard® *Express* impregnates the substrate without forming a film, so the substrate remains permeable to air and water vapour. Once dry, ImperGuard® *Express* is colourless. It is also UV-resistant and does not yellowish with time.

USE

ImperGuard® *Express* is recommended for all exterior and interior vertical and horizontal surfaces made of untreated concrete (regular concrete, precast, fibre-reinforced, UHPC, GRC) older than 24 hours.

ADVANTAGES AND CHARACTERISTICS

- Apply 24 hours after implementation. Avoids the 28-days curing period: concrete can be treated and delivered in 48 hours!
- Water-repellent & anti-efflorescence: prevents water from penetrating and greatly reduces efflorescence and damages caused by freezing and thawing.
- Non-film-forming, allows substrate to breathe.
- UV-resistant.
- Ready-to-use, single-component product.



ENVIRONMENT

Environment-friendly product:

- Water-based product.
- Non hazardous: no petroleum-based solvents.
- 90% biodegradable.
- VOC < 2 g/l*.

CHEMICAL NATURE

Aqueous emulsion based on silane, siloxane and acrylic resins.

CONTAINERS

5 and 25 litres cans.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Appearance	: Milky
Odour	: Odourless
pH	: 8 ± 0.5
Boiling point [°C]	: 100 °C
Density	: 1.00 ± 0.02
Solubility in water [vol/vol]	: Total
Flash point [°C]	: Not applicable

HOW TO USE

Surface preparation:

- Apply the product to concrete that has been freshly demoulded for more than 24 hours. The surface must be clean, free of dust, efflorescence and mould release oil residues.
- If the surface requires prior cleaning for the reasons mentioned above, clean with **Guard Cleaner® Surface Preparation** and/or **Guard Cleaner® Maintenance**. On concrete that has dried for more than 48 hours, cleaning must be carried out.
- Rinse carefully with a pressure washer until the surface is free from all traces of the cleaner.
- Allow to dry for at least 12 hours before applying the protection.

Application:

- Use neat - do not dilute.
- Shake the product well before use
- Always carry out a full preliminary test under actual conditions of use on a small surface to check effectiveness and compatibility with the substrate.
- Apply to saturation in two wet-on-wet coats.
- On vertical surfaces, apply from the bottom up.

- Do not overload the substrate, remove any excess before drying.
- Protected drying and palletisation time under film: 24 hours.
- Optimum effectiveness obtained after 7 days.

For more information refer to the technical specifications.

APPLICATION TOOLS

Apply using a low-pressure sprayer, roller or brush.



COVERAGE

Coverage depends on the porosity of the concrete. The figures below should be used only as a general guideline (final coverage):

160 to 200g/ m² or 5 to 6 m² / L.

CLEANING YOUR EQUIPMENT

Clean tools and equipment immediately after use with water.

STORAGE

- Keep in a dry place (between 5°C and 30°C).
- Storage: 12 months following the production date when kept in the original unopened container.

RECOMMENDATIONS

- Only treat surfaces previously cleaned of all atmospheric pollution and stains.
- Do not apply to concrete with very low porosity, polished, glazed, organic, metallic or waterproofing materials.
- In some cases, the product may give a slight wet look effect.
- For a perfect application and effective protection, ImperGuard® Express must be used on a support having a temperature between 10°C and 30°C, a humidity level less than or equal to 5% and a pH between 7 and 10.
- Do not apply in rainy weather, very hot weather or in full wind. Air temperature between 10°C and 30°C. Hygrometry rate: between 30% and 80% RH (relative humidity). Check for the absence of precipitation within 24 hours of the work.
- Provide protection for the surrounding supports and protection for the applicator.
- Environmental protection and packaging: dispose of empty packaging at a waste disposal centre. Never dispose of packaging in the environment.
- Do not dilute or mix with any other product.

HEALTH AND SAFETY

For intensive use, refer to paragraph 8.2 of the safety data sheet.

- Respiratory protection : Under normal conditions of use where adequate ventilation is available, no special respiratory protection equipment is needed.
- Hand protection : Wear latex gloves.
- Skin protection : Wear protective clothing with long sleeves.
- Eye protection : If there is a real risk of splashing, wear protective goggles.
- If swallowed : Do not induce vomiting. Contact a doctor or a specialist.

PRODUCT FOR PROFESSIONAL USE ONLY

TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE
Tél: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89
E-mail : contactus@guardindustry.com
www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated : 21/10/2024