



WOODGUARD®

Revitalizer



REVIVES AND CLEANS WOOD

- LIGHTENS GREYED WOOD
- REMOVES GREASE AND DIRT
- ALL TYPES OF WOOD: PINE, SPRUCE, DOUGLAS FIR, OAK, IPE, TEAK...

- QUICK EFFICIENCY IN 15 MIN
- TERRACE - DECK - CLADDING - FURNITURE
- EXTERIOR

PRODUCT DESCRIPTION

WoodGuard® Revitalizer is a cleaner that removes oxidised wood cells caused by time and weathering, while giving it a new lease of life. Its penetrating power results in a rapid action that removes greying and dirt without discolouring the wood.

USE

WoodGuard® Revitalizer can be used outdoors on dry or slightly damp wood without any traces of paint.

WoodGuard® Revitalizer is ideal for treating all untreated wood: joinery or wooden objects, garden furniture, shutters, coverings, terraces, gratings, joinery, fences, garden sheds, fences garden sheds, fences, palisades, etc.

CHEMICAL NATURE

- Water-based product formulated with oxalic acid.

ADVANTAGES AND CHARACTERISTICS

- Non flammable.
- Easy and quick to apply.
- Ready to use.
- Can be used on all types of woods.
- Water-based product.
- Petroleum solvent-free.
- Revives greying woods.
- Efficient in 15 minutes.

CONTAINERS

5 litres.



TECHNICAL DATA

Physical state at 20 °C	: Viscous liquid
Colour	: Clear
Odour	: Light
pH	: 2 ± 0.5
Boiling point [°C]	: 100°C
Relative density	: 1.04 ± 0.015
Solubility in water [vol/vol]	: Total
Flashpoint [°C]	: Not applicable
VOC rate	: < 50 g/L*

HOW TO USE

- Use neat: do not dilute.
- Shake the product well before use.
- Always carry out a preliminary test.
- Generously apply to the wood to be treated.
- On vertical surfaces, apply from top to bottom.
- In the event of application on furniture and intricate woodwork or small surface, apply little by little using a brush or a paintbrush.
- Allow the product to act for 10 to 15 minutes, and then rinse thoroughly with water until the product is fully eliminated.
- Scrubbing with a nylon brush may improve the effectiveness of the product.
- If necessary, reapply the product following the same procedure.

APPLICATION TOOLS

Apply with a brush or a roller.



COVERAGE

The values below are indicative:

5 to 8 m² / litre

CLEANING YOUR EQUIPMENT

Clean used tools and equipment with water immediately after use.

STORAGE

- Store in a dry place at a temperature of between 5°C and 25°C.
- Shelf-life: 24 months from date of manufacture, in original unopened can.

PRECAUTIONS FOR USE

- Do not apply in rainy or hot weather. Surface and air temperature should be between 5°- 30°C.
- Do not dilute or mix with other products.
- Corrosive product: it is recommended to wear safety goggles, gloves and protection clothing.
- **WoodGuard® Revitalizer** does not remove the green traces on autoclave wood.
- Rinse thoroughly with water before applying a coating.
- In case of brushing or rinsing with a high pressure washer, always follow the wood grain.
- Do not lay the wood to be treated onto surfaces in order to avoid it becoming soiled.
- Protect vegetation.
- If crystals appear after drying, rinse them away with water.

HEALTH AND SAFETY

For intensive use, refer to paragraph 8.2 of the safety data sheet.

- Breathing protection: No breathing protection equipment is required under normal use conditions with suitable ventilation.
- Hand protection: Wear chemical resistant gloves (neoprene, PVC).
- Skin protection: Wear long-sleeved protection clothing.
- Eye protection: Wear protective goggles.
- In case of ingestion: Do not induce vomiting. Contact a doctor or specialist.

KEEP OUT OF REACH OF CHILDREN

TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE
Tel: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89
E-mail : contactus@guardindustry.com
www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website
www.guardindustry.com

Last updated : 10/05/2023