

GUARD TECH DECAPFIX®



ULTRA-FAST CONCENTRATED CONCRETE REMOVER

- HIGHLY ACTIVE STRIPPER**
- EXPRESS ACTION & EFFECTIVENESS**

- NON-HARMFUL AND CMR-FREE**
- BIODEGRADABLE**
- DOES NOT DAMAGE SURFACES: METAL, PAINT, RUBBER**

PRODUCT DESCRIPTION

GT DécapFix® is a powerful, fast-acting remover specially designed to effectively remove concrete, cement and laitance residues from all construction equipment.

Thanks to its concentrated formula, GT DécapFix® is a very economical solution: it can be diluted up to 1 part product to 5 parts water while maintaining optimal effectiveness.

Its innovative formulation makes it less aggressive and more advantageous than traditional hydrochloric acid-based products. With no unpleasant odour for the user, GT DécapFix® does not cause rust on equipment, attack aluminium, tarnish paint or bleach plastics.

USE


Ideal for maintaining construction equipment: concrete plants, mixer trucks, concrete skips, props, etc.

ADVANTAGES AND CHARACTERISTICS

- Powerful, fast-acting stripper.
- Concentrated formula, economical to use.
- Can be diluted up to 1 part product to 5 parts water.
- Less aggressive than hydrochloric acid-based products.
- No unpleasant odour for the user.
- Does not cause rusting of equipment.
- Does not attack aluminium.
- Does not tarnish paintwork.
- Does not bleach plastics.

PACKAGING

- 6 Kg drums.
- 25 Kg drums.
- 250 Kg barrels.



CHEMICAL NATURE

Formulation based on organic compounds.

TECHNICAL DATA

Physical state at 20 °C	: Liquid
Colour	: Light yellow
Odour	: Characteristic
pH	: 1.5 ± 0.5
Relative density	: 1.37 ± 0.02
Solubility in water [vol/vol]	: Total
Flashpoint [°C]	: Not applicable
VOCs	: < 1 g/l

HOW TO USE

- It is essential to carry out preliminary tests before application.
- Concentrated product, do not use undiluted.
- Shake the container well before use.

Recommended dilution:

Depending on the level of soiling, dilute **GT DécapFix®**:

- Maximum dilution ratio: 1 part product to 5 parts water.
- Always mix in the following order: pour the water into the container first, then add the product. Mix mechanically for 5 minutes before application.

Application:

- Apply the product using a scrubbing brush, brushing the surface to remove any residue.
- Rinse the entire surface, preferably with a high-pressure cleaner or, if necessary, with a water jet while brushing.
- It is not necessary to neutralise after rinsing.

APPLICATION TOOLS

Apply with a scrubbing brush or spray bottle.



COVERAGE

The following values are for guidance only:

6 to 8 m²/ kg of ready-to-use product.

CLEANING YOUR EQUIPMENT

Tools and equipment should be cleaned with water immediately after use.

STORAGE

- Store in a dry place at a temperature of between 5°C and 30°C.
- Shelf-life: 24 months from date of manufacture, in original unopened drum.

PRECAUTIONS FOR USE

- Wear gloves, protective clothing and goggles.
- Do not allow to dry.
- Do not mix with any other product.
- For best results, **GT DécapFix®** must be used when the surface temperature is between 5°C and 30°C.
- Do not apply in rainy or very hot weather. Air temperature between 5°C and 30°C.

HEALTH AND SAFETY

In case of intensive use, refer to section 8.2 of the safety data sheet.

- Breathing protection: No breathing protection equipment is required under normal use conditions.
- Hand protection: Wear chemical-resistant gloves (neoprene, PVC or similar).
- Skin protection: Wear clothes that will protect the skin and have long sleeves.
- Eye protection: Wear protective goggles.
- In case of ingestion: Do not induce vomiting. Contact a doctor or specialist.

FOR PROFESSIONAL USE ONLY



TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere
31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com

www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industry guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industry products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated : 08/01/2026