



GUARDTECH®

**CMR-FREE
CERTIFIED**

CONCENTRATED DEGREASING SHAMPOO FOR CONSTRUCTION EQUIPMENT

✓ CLEANS AND DEGREASES**✓ POWERFUL AND FAST****✓ ULTRA CONCENTRATED****✓ DOES NOT ALTER SURFACES**

DESCRIPTION

GT Yellow Max® is a very effective degreasing shampoo to remove grease, oil, soot and brake dust from all construction equipment.

GT Yellow Max® is also effective for deep cleaning of trim (doors, roofs, ...). The product is excellent for cleaning insects from windshields. Contains also an anti-scale agent which avoids the calcification of the apparatuses, and limits the traces on the supports.

GGT Yellow Max® is formulated without solvents and is safe for paints, rubber, glass, fabric and coverings.

USE

GT Yellow Max® is ideal for trucks, bodies, tarps, engines, chassis, hard surfaces, painted surfaces, rims, under-hood components and a variety of construction equipment and machinery.

CHEMICAL NATURE

Mixture of silicates and surfactants.

BENEFITS AND FEATURES

- Fast-acting, multi-purpose degreaser.
- Advanced solvent-free formula for fast, safe cleaning.
- Contains an anti-static and anti-scaling agent
- Safe for paints, rubber, glass, fabric and coverings.
- Removes polymer from trucks and floors.

PACKAGING

Cans of 25L.
200L drums.
Tanks of 1000L.



TECHNICAL DATA

Physical state at 20 °C	: Liquid
Color	: Yellow
Smell	: Pleasant
pH	: > 10
Density	: 1.05 ± 0.01
Solubility in water [vol/vol]	: Total
VOCS	: < 1 g/l

APPLICATION

- Pre-testing and wearing personal protective equipment is essential.

High pressure cleaner:

- Prepare a detergent solution in the machine's tank and adjust the machine to obtain a concentration between 5 and 8% at the end of the lance. Apply the product from bottom to top on the surface.
- Wait 2 to 3 minutes for the product to act. Rinse with the high pressure cleaner from bottom to top.

Low pressure sprayer:

Recommendation for dilution:

- Very dirty surface = 1L of product for 9L of water.
- Dirty surface = 1L of product for 19L of water.
- Spray evenly from bottom to top with a low pressure sprayer.
- Leave to act for 2 to 3 minutes.
- Rinse thoroughly from bottom to top with a high pressure cleaner.

APPLICATION TOOLS

Apply with a high pressure cleaner or a low pressure sprayer.



COVERAGE

The values below are given as an indication for 1 liter of product ready to use:

3 to 5 m² / liter.

EQUIPMENT CLEANING

Clean tools and equipment with water immediately after use.

STOCKAGE

- Store in a dry place at a temperature between 5°C and 30°C.
- Shelf life : 24 months from the date of manufacture, in original unopened packaging.

PRECAUTIONS FOR USE

- Do not allow to dry on the surface.
- Do not mix with other products.
- Do not use on raw aluminum.
- In concentrated form, this product can mat paint, varnish and glass surfaces.
- Do not apply on hot bodies or in direct sunlight. For a perfect application, **GT Yellow Max®** must be used when the temperature of the supports is between 5°C and 30°C.
- Do not apply in rainy or very hot weather. Air temperature between 5°C and 30°C.
- Guard Industrie cannot be held responsible for a too low dilution or a bad rinsing on the support. Always do a test beforehand.

HEALTH / SAFETY

For intensive use, refer to paragraph 8.2 of the safety data sheet.

- Respiratory protection: No respiratory protective equipment is required under normal conditions of use.
- Hand protection: Wear chemical resistant gloves (neoprene, PVC...).
- Skin protection: Wear long-sleeved skin protection clothing.
- Eye protection: Wear safety glasses.
- If swallowed: Do not induce vomiting. Contact a doctor or specialist.

PROFESSIONAL USE ONLY



TECHNICAL SUPPORT

GUARD INDUSTRY

695B Rue de l'Hers - ZA de la Masquere

31750 ESCALQUENS • FRANCE

Tél: +33 (0)1.55.86.17.60 • Fax:+33 (0)1.48.58.16.89

E-mail : contactus@guardindustry.com - www.guardindustry.com

Important: The content of this documentation is based on our experience with the product. Guard Industrie guarantees the quality of its products but expressly disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Guard Industrie products, or adverse weather conditions. For more information, consult the safety data sheet.

For the most recent version of our data sheet, visit our website www.guardindustry.com

Last updated : 10/01/2025